

Gillmore Apparatus

UTCM-0058

The UTCM-0058 Gillmore Apparatus is used to determine the setting time of cement hydraulic hydrometer lime and mortar. Apparatus consists of two horizontally positioned arms, carrying weighted needles, initial needle has a 2.12 mm diameter and 113.4 g in weight and the final needle has a 1.06 mm diameter and 453.6 g in weight.



Technical Specifications

Dimensions300x100x300 mmWeight (approx.)2.5 kg

About PCTE

PCTE have over 30 years' experience in the measurement and testing of construction materials. PCTE can provide more than just the equipment, they can provide expert training. PCTE have a service centre in Sydney in which they can provide calibration, repairs and warranty repairs.

Other Equipment

PCTE supply three main ranges: NDT, Lab and Geotech Instrumentation.

NDT includes: Rebound Hammers, Covermeters, Ultrasonics, GPR, Corrosion Testing, Coating Testing and Foundation Testing

Lab includes equipment for: Concrete, Cement, Aggregate, Soil, Asphalt and Metal

Geotech Instrumentation includes: Strain Gauges, Piezometers, Inclinometers, Extensometers, Tiltmeters, Load Cells and Dataloggers

Perth: 0408 034 668 Sydney: 0418 381 709 Melbourne: 0428 315 502 Brisbane: 0419 477 715 Auckland: 64 274 738758 www.pcte.co.nz